



## E1/T1/J1 Digital VoIP Gateway GXW4500 Series

The GXW4500 series are E1/T1 Digital VoIP Gateways that allow digital PSTN and ISDN trunks to be integrated with VoIP networks. By connecting the GXW4500 series with a VoIP network and a traditional PBX or E1/T1 provider, businesses can drastically increase the amount of PSTN/ISDN trunks integrated with their VoIP network. The GXW4500 series offers three models that provide 1, 2 or 4 E1/T1/J1 spans and support 30, 60 or 120 concurrent calls to cater to the VoIP needs of large and medium sized enterprises.



### Gigabit


Dual Gigabit auto-sensing RJ45 network ports with integrated NAT router



TLS and SRTP security encryption technology to protect calls and accounts



Automated provisioning by HTTP/TFTP with XML config files



Software configurable E1/T1/J1 ports, support PRI, SS7, MFC R2



Supports a wide-range of voice codecs, including G.722, G.729, iLBC, and more



Supports T.38 Fax for creating Fax-over-IP



Supports multi-language voice prompts



Supports up to 120 concurrent calls

<b>E1/T1/J1 Interface</b>	1/2/4 RJ45 ports, supporting up to 30/60/120 simultaneous VoIP calls
<b>Network Interfaces</b>	Dual self-adaptive Gigabit ports (switched or routed)
<b>Peripheral Ports</b>	(2) USB 3.0, (1) SD card interface
<b>LED Indicators</b>	LAN, WAN, E1/T1/J1
<b>LCD Display</b>	128x32 dot matrix graphic LCD with DOWN and OK buttons
<b>Reset Switch</b>	Yes, long press for factory reset and short press for reboot
<b>Voice &amp; Video Capabilities</b>	
<b>Voice-over-Packet Capabilities</b>	LEC with NLP Packetized Voice Protocol Unit, 128ms-tail-length carrier grade Line Echo Cancellation, Dynamic Jitter Buffer, Modem detection & auto-switch to G.711
<b>Voice and Fax Codecs</b>	G.711 A-law/U-law, G.722, G.723.1 5.3K/6.3K, G.726, G.729A/B, iLBC, AAL2-G.726-32
<b>Fax over IP</b>	T.38 compliant Group 3 Fax Relay up to 14.4kpbs and auto-switch to G.711 for Fax Pass-through, Fax data pump V.17, V.21, V.27ter, V.29 for T.38 fax relay
<b>Voice-quality Enhancement</b>	Echo cancellation (G.168-2004), Jitter buffer, Silence suppression (VAD, CNG), PLC
<b>QoS</b>	Layer 2 QoS (802.1Q, 802.1p) and Layer 3 (ToS, DiffServ, MPLS) QoS
<b>Signaling &amp; Control</b>	
<b>DTMF Methods</b>	In-band audio, RFC2833, and SIP INFO
<b>Digital Signaling</b>	SIP (RFC 3261) over UDP/TCP/TLS, PRI, SS7, MFC R2, RBS (pending) PRI switch types: Euro ISDN, nation, Q.SIG CAS: MFC R2 (Argentina, Brazil, China, Czech Republic, Colombia, Ecuador, Indonesia, ITU, Mexico, Philippines, Venezuela) SS7: ITU, ANSI, China
<b>Upgrade</b>	Firmware upgrade via TFTP / HTTP / HTTPS or local HTTP upload
<b>Device Management</b>	Syslog, HTTPS, Web browser, voice prompt, TR-069 management, backup and restore, port capture and packet capture
<b>Network Protocols</b>	TCP/UDP/IP, RTP/RTCP, ICMP, ARP, DNS, DDNS, DHCP, NTP, TFTP, SSH, HTTP/HTTPS, PPPoE, STUN, SRTP, TLS, LDAP, PPP, Frame Relay (pending), IPv6, OpenVPN®
<b>Status and statistic</b>	Call status and history, device status monitoring and ISDN status monitoring
<b>Security</b>	
<b>Media Encryption</b>	SRTP, TLS, HTTPS, SSH, 802.1X
<b>User-defined ports</b>	SIP port, RTP port, HTTP/HTTPS port
<b>Advanced Defense</b>	Fail2ban, alert events, Whitelist, Blacklist, strong password based access control
<b>Physical</b>	
<b>Universal Power Supply</b>	Input: 100 ~ 240VAC, 50/60Hz; Output: DC+12V, 2A
<b>Physical &amp; Dimensions</b>	GXW4501: Unit Weight: 2,350g; Package Weight: 3130g GXW4502: Unit Weight: 2360g; Package Weight: 3140g GXW4504: Unit Weight: 2380g; Package Weight: 3160g Unit Dimensions: 485mm(L) x 191mm(W) x 46.2mm (H)
<b>Temperature and Humidity</b>	Operating: 32 - 113°F / 0 ~ 45°C, Humidity 10 - 90% (non-condensing) Storage: 14 - 140°F / -10 ~ 60°C, Humidity 10 - 90% (non-condensing)
<b>Mounting</b>	Rack mount & Desktop
<b>Additional Features</b>	
<b>Multi-Language Support</b>	Web UI: English, Simplified Chinese, Traditional Chinese, Spanish, French, Portuguese, German, Russian, Italian, Polish, Czech; Customizable IVR/voice prompts: English, Chinese, British English, German, Spanish, Greek, French, Italian, Dutch, Polish, Portuguese, Russian, Swedish, Turkish, Hebrew, Arabic; Customizable language pack to support any other languages
<b>Compliance</b>	FCC 47 C.F.R FCC Part 15 Class B 47 C.F.R FCC Part 68 (TIA-968-B Section 5.2.4 (T1+ISDN)) CE EN 55032, EN 55035, EN 61000-3-2, EN 61000-3-3, EN 60950-1, TBR 4 (E1+ISDN), TBR 12 (E1), TBR 13 (E1+ISDN) RCM AS/NZS CISPR 32, AS/NZS 61000.3.2, AS/NZS 61000.3.3, AS/NZS 60950.1, AS/ACIF S016(E1), AS/ACIF S038(E1+ISDN) Other ITU K.21 (Enhanced Levels); UL 60950-1 (Power adapter)